

## FIBER ADAPTERS

Datacom fibre adaptors are available for all standard connector types in both single mode and multimode duplex range. Single mode adaptors are available in Zirconia and Multimode adaptors are available with phosphor Bronze sleeves.

SC DUPLEX ADAPTER



LC DUPLEX ADAPTER



## COMPLIANCE

ANSI/TIA 568-C.3

## PHYSICAL CHARACTERISTICS

Dust cover	SC Black Color, LC White Color
New SC/LC One Piece Type	Multimode/Singlemode
Bush	Aluminium
Clip	Stainless Steel
Ferrule type	Multimode-Phosphor Bronze, Singlemode-Zirconia
Boot	TPE, Blue Color (3.0mm)

## PERFORMANCE CHARACTERISTICS

Durability	500 Cycles
Vibration	10to 55 Hz 1, 5mm Double Amplitude
Tensile Strength	10 kgf
Insertion Loss	<.2dB (Singlemode) / 0.3dB (Multimode)-SC /LC
Operating Temperature:	(-)20° to +70°
Temperature Cycle	(-)40° to +80°

## ORDERING INFORMATION

Description	Order Code
Fibre Adaptors SC Duplex MM PB Sleeve Ivory	DC-ADSC-MM-D-IV
SC Duplex OM3 Adaptor PB Sleeve Aqua	DC-ADSC-M3-D-AQ
LC Duplex OM4 Adapter PB Sleeve Aqua	DC-ADLC-M4-D-AQ
SC Duplex SM Adaptor Zirconia Sleeve Blue.	DC-ADSC-SM-D-BL
LC Duplex MM Adaptor, Ivory SC Cutout	DC-ADLC-MM-D-IV
LC Duplex OM3 Adaptor PB Sleeve Aqua	DC-ADLC-M3-D-AQ
SC Duplex OM4 Adaptor PB Sleeve Aqua	DC-ADSC-M4-D-AQ
LC Duplex SM Adaptor Blue SC Cutout	DC-ADLC-SM-D-BL
SC/APC Duplex SM Adapter, Zircon Sleeve, Green, SC Cutout	DC-ADSA-SM-D-GN